





B**BROADRIB**from our
FIBRE BONDED RANGE

BROADRIB

MADE IN THE UK. MADE TO LAST.

Specification

PRODUCT	Broadrib Heavy Contract Carpet, Tiles and Planks
FIBRE CONSTRUCTION	80% Polypropylene, 15% Polyamide, 5% Polyester
WEIGHT	1020gm metre ² (Sheet), 4020gm metre ² (Tile and Plank)
THICKNESS	7.50mm (Sheet), 8.0mm (Tile and Plank)
ROLL WIDTH	 2m and 4m. Ribbing runs down length of roll
TILE SIZE	 50cm x 50cm (Tiles are Bitumen backed)
PLANK SIZE	 25cm x 100cm (Tiles are Bitumen backed) Plank orders are subject to a minimum order quantity of 500m ² due to manufacturing complexities. The minimum order quantity can be any combination of product and colour.
COLOUR FASTNESS	Light (BS EN ISO 105:802) >6 Wet Rubbing (BS EN ISO 105:B01) 5 Dry Rubbing (BS EN ISO 105:X12) 5
FLAMMABILITY	(BS5287) Assessment and labelling of Textile Floorcoverings tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char
BS EN 13501	Euroclass C _{fl} -s1 (Sheet) Euroclass C _{fl} -s1 (Tile) Euroclass B _{fl} -s1 (Plank)
REDUCTION IN IMPACT NOISE	BS EN ISO 140-8:20dB (Sheet)
ANTISTATIC	Suitable for use in computer rooms
INSTALLATION	 The method of installation should conform to BS5325. For details of subfloor preparation and a full guide to installation visit: www.heckmondwike-fb.co.uk . Before laying Broadrib, tiles and planks should be allowed to condition for 24 hours at the expected temperature and humidity levels. Broadrib tiles should be laid rotationally, alternating the direction of the tiles through 90°. For Broadrib plank installation guidance, please visit www.heckmondwike-fb.co.uk
ADHESIVE GUIDE	Sheet carpet should be fully adhered with F. Ball F3 or F52 or Bostik Laybond Carpet Adhesive. Sheet carpets can be laid into F40 as a release system. For tiles and planks, use F. Ball 41 or Bostik Laybond Carpet Tile Tackifier.
MAINTENANCE	To achieve maximum life expectancy, it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: www.heckmondwike-fb.co.uk

PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Fibre compositions of colours within ranges may vary. Heckmondwike reserves the right to change or modify product specifications without giving prior notice.

