go to carpet tiles

Burmatex

MANUFACTURERS OF CREATIVE FLOORING

technical specifications

Product Description
Pile Yarn Description
Tile Dimensions
Pile Yarn Weight
Total Weight
Pile Height
Total Thickness
Construction

Tufts per m2 / Pile Density Backing Description Wear Classification Luxury Rating Class

Flammability

Thermal Resistance

Castor Chair Rating
Hexapod
Static Loading
Dynamic Loading
Body Voltage Test
Colour Fastness To Ligh

Colour Fastness To Light Colour Fastness To Shampoo Sound Absorption Coefficient Reduction in Impact Noise Reduction in Impact Noise at 1000Hz

Number Of Tiles Per Box

VOC Warranty

····· ••• •••











20 (5m²)

Class A+

15 years



Low Carbon Level Loop

Tufted 1/10th gauge loop

BS ISO 6356:2000 <2kV

BS EN ISO 10140-3:2010 20dB

BS EN ISO 10140-3:2010 27.5dB

50cm x 50cm

500g/m²

3810g/m²

196,850/m²

Euroclass Bfl-s1

Tog Rating: 0.42

BS EN 354:2003

3.0mm

5.5mm

IC1

EqoCycle® 75 recycled solution dyed nylon

BioBase™ backing (recycled EN 14021)

BS ISO 10361: Method B:2000 3 to 4

BS EN ISO 105 - B02 Minimum Grade 6

BS 1006:UK-TB: 1990 Minimum Grade 4-5

class 33 heavy commercial use (BS EN 1307)

BS EN 985 Pass - suitable for continuous use

BS 4939: 1987 (2003) Recovery >80% (24hrs)

BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)













CE



go to

t











We are committed to helping deliver a sustainable future, because we believe that what we do **matters**. To help us deliver on this commitment, we have developed **eco_matters*** sustainability goals, supported by the independently 3rd party verified **eco_matters*** ecosystem.



Journey to Net Zero & Beyond



Positive Environmental Impact



Social Values & Well Being

Made from EqoCycle® 75 recycled solution dyed nylon, and our unique BioBase™ recycled backing, go to delivers class 33 Heavy Commercial Use performance at unrivalled value. Supported by high stock levels, and rapid delivery, the 20 colour palette of coordinating plains and stripes provides versatility for use in any space.



go to is low carbon



go to uses EqoCycle® 75 recycled yarn



arctic uses BioBase™ recycled backing



our products contribute towards Leed accreditation







SKA our products adhere to SKA standards

Burmatex® reco^overy take back service provides a no landfill solution for your used tiles

Burmatex® products are made using 100% certified **renewable** electricity

ecomatters* ecosystem is independently 3rd party verified

WELL Building Standards
Our products contribute to
WELL Building Standards

contact us T +44 (0) 1924 262 525 F +44 (0) 1924 280 033 email: projects@burmatex.co.uk

our products are supported

by a 3rd party verified EPD

Burmatex Ltd Victoria Mills, The Green Ossett, West Yorkshire WF5 OAN, United Kingdom

www.burmatex.co.uk





LRV values

Product code	Product colour name	CIE Y	CIE L
21801	jet black	3.01	20.09
21802	coal grey	5.21	27.34
21803	medium grey	9.19	36.35
21806	sea blue	6.45	30.52
21810	sky blue	12.13	40.96
21811	green	16.80	48.49
21813	light beige	21.14	53.64
21814	medium beige	13.20	43.04
21815	dark beige	9.07	35.97
21816	metal grey	6.27	30.04
21817	light grey	13.98	44.16
21818	moss green	12.53	42.02
21819	orange	12.04	41.23
21820	red	4.68	25.62
21821	purple	6.67	31.04
21822	deep blue	5.74	28.68
21902	coal grey stripe	10.36	38.48
21903	medium grey stripe	6.49	30.61
21906	sea blue stripe	4.83	26.25
21915	dark beige stripe	6.03	29.16

