

MODULAR T5 COMMERCIAL LVT

Technical Data

CLASSIFICATION	STANDARD	MODULAR T5
Classification	EN ISO 10582	Compact Resilient Floorcovering
	EN ISO 10874	Residential: 23 - Commercial: 33 - Industrial: 42
Wear layer binder content	EN ISO 10582	Type I
TECHNICAL CHARACTERISTICS		
Total thickness	EN ISO 24346	2.2 mm
Total weight	ISO 29997-EN430	3.0 kg/m ²
Wear layer thickness	EN ISO 24340	0.55 mm
Installation type		Glue-Down
Bevelled edges		4V Microbevel
Surface treatment (PUR)		TopClean XP™
Material group - Form of delivery	ISO 24342	Plank : 20 x 120 cm = 19 planks/box = 4.56m ² /box Mini-Plank : 15 x 60 cm = 56 tiles/box = 5.04 m ² /box
PERFORMANCES FOR CE MARKING REQUIREMENTS (EN 14041)		
Declaration of Performance	EN 14041	012701-0064-DoP-2021-07
Reaction to fire	EN ISO 13501-1	B _f s1 on concrete substrate
Electrostatic properties	EN 1815 / EN 1081	<2 kV on concrete / 1 x 10 ⁹ Ohm
Thermal resistance	EN ISO 10456	0.03 m ² K/W
TECHNICAL PERFORMANCES		
Dimensional stability	EN ISO 23999	≤ 0.10%
Impact sound reduction	EN ISO 717-2	ΔL _w 3 dB
Slip resistance	DIN 51130	R10
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Curl resistant to heat	EN ISO 23999	≤ 2 mm
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6
Residual indentation	EN ISO 24343-1	≤ 0.10 mm
Chemical resistance	EN ISO 26987	Very good
Underfloor heating		Suitable – max. 27°C
ENVIRONMENTAL PERFORMANCE		
Total VOC emissions	ISO 16000-9	≤ 100 µg/m ³ (after 28 days)
Recyclable		100%



This technical information may be subject to modification for the benefit of further improvement.
Tarkett's instructions on installation and maintenance should be observed, see our website for details.
A slight colour and / or gloss variation may be detectable between sample and delivered materials. E&OE.