




#### Installation Method



Ashlar

Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Yuton 105 **Colour** Ice **Collection** Yuton Collection **Backing** CQuest™Bio

#### Product Specifications

Product Construction	Tufted Patterned Structured Loop Pile
Yarn System	100% Solution Dyed Nylon
Standard Backing	CQuest™Bio
Size	50cm x 50cm
Tiles per Box	16 - 4m <sup>2</sup>
Optional Backings	<a href="#">CQuest™Bio SONE</a>

#### More Product Specifications

Pile Yarn Weight	551 g/m <sup>2</sup> ± 5%
Total Weight	3,622 g/m <sup>2</sup> ± 5%
Pile Height	3.2 mm +15% / - 10%
Total Thickness	5.9 mm ±0.5mm
Gauge - Ends per 10 cm	1/10 - 39.4
Tufts per m <sup>2</sup>	178409 /m <sup>2</sup> ±5%

#### Performance Specifications


















Wear Classification	EN 1307 33 Heavy Contract
Castor Chair Rating	≥2.4 (EN 985) Continuous Use
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)
Light Fastness	≥7 (ISO 105-B02)
Light Reflectance Value (LRV-L)	45.00
Light Reflectance Value (LRV-Y)	14.55
Dimensional Stability	≤0.2% (ISO 2551/EN 986)
Impact Sound Insulation ΔLw EN ISO 10140-3	24 dB
Rating of Sound Absorption (αw) EN ISO 11654	0.15
Sound Absorption (αs) EN ISO 354 at 125 Hz	-0.01
Sound Absorption (αs) EN ISO 354 at 250 Hz	0.02
Sound Absorption (αs) EN ISO 354 at 500 Hz	0.04
Sound Absorption (αs) EN ISO 354 at 1000 Hz	0.15
Sound Absorption (αs) EN ISO 354 at 2000 Hz	0.27
Sound Absorption (αs) EN ISO 354 at 4000 Hz	0.32

#### Environmental Specifications

Environmental Product Declaration	<a href="#">Download EPD</a>
Total Recycled Content	63.4 %
Pre-Consumer (Total)	63.40 %
Post-Consumer (Total)	0.00 %
Yarn Recycled Content	0.00 %
Pre-Consumer (Yarn)	0.00 %
Post-Consumer (Yarn)	0.00 %
Total Bio Based Content	10.46 %
Total Recycled & Bio Based Content	73.86 %
Indoor Air Quality	<a href="#">Compliant with LEED EQ 4.3 credit</a> French A+ <a href="#">GLP 100209</a> <a href="#">M1 Emission Certification -CQB</a>
Indoor Air Quality GUI	<a href="#">GUI Standard</a>

HQE (France)	<a href="#">View Potential HQE Contribution</a>
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>
Embodied Carbon (Cradle to Gate)	6.58 kg CO <sub>2</sub> eq./m <sup>2</sup>
Full Life Cycle Carbon	Certified Carbon Neutral Floors™
Installation Waste	Ashlar – 3-5 % Monolithic – 3-4%
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.
<b>Technical Information</b>	
Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	ISO 9001, 14001 & 45001 Certified Facilities in Europe

### Certifications

 DOP: 1037/127362 EN 14041:2004 Notified Body - 0459 COC 0493 - CPR - 0181 For use as floor covering in buildings	 DOP: 1037/127362 EN 14041:2004 Approved Body - 85112 COC 85112/CPR/0181 For use as floor covering in buildings			 L B <sub>1-s1</sub> NCS	 ≥0.30
 <2.0 kV	 <10 Ω	 24 dB	 0.15	 ≥ 7	
 0.07	 ≥2.4			 EMISSION DANS L'AIR INTERIEUR A+ A B C	